

Vertical
Laminar flow
Cabinet




LCD Display
Airflow velocity, UV timer, UV work time, system work time, real time.



Waterproof Socket
2 waterproof sockets are located in the side panel, for optimum convenience of using small devices inside the cabinet .



Gas Tap



UV Lamp
Emission of 253.7 nanometers for most efficient decontamination.



Side Glass Window
The transparent side glass windows maximize light and visibility inside the cabinet, providing a bright and open working environment.

TECHNICAL PARAMETERS

Model	BBS-V1300	BBS-V1800
External Size (W*D*H)	1300*750*2040mm	1800*750*2040mm
Internal Size (W*D*H)	1200*645*610mm	1700*645*610mm
Work Surface Height	750mm	
Display	LCD Display	
Airflow Velocity	Average of 0.3~0.5m/s	
Material	Main Body: Cold-rolled steel with anti-bacteria powder coating Work Table: 304 stainless steel Side and Front Windows: 5mm toughened glass anti-UV	
Pre-Filter	Polyester fiber, washable	
HEPA Filter	99.999% efficiency at 0.3µm	
Noise	<65dB	
Front Window	Motorized	
Max Opening	430mm	430mm
LED Lamp	12W*1	16W*1
UV Lamp	30W*1	40W*1
	Emission of 253.7 nanometers	
Consumption	400W	450W
Waterproof Socket	Two, total load≤500W	
Caster	Universal caster with leveling feet	
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz	
Standard Accessory	LED lamp, UV lamp*2, Base stand, Gas Tap, Waterproof socket*2	
Optional Accessory	Electric height adjustable base stand	
Gross Weight	228kg	306kg
Package Size (W*D*H)	1460*1070*1650mm	1960*970*1600mm